

Model: 		*2MP smart cloud camera (excluding TF Card) X 1 * Specification X1 * Screw pack X1 * stents X1 * Power adapter X1 * Power cord X1
Specification parameter		
system	Main Processor	dual-core 32-bit DSP (XM650V200), pure hard compression, watchdog
	image sensor	2 2m 1/2.8" SC233A High performance CMOS sensors
	Operation System	Embedded LINUX operating system
	Video Compression	Smart H.265X
	APP	lcsee (Android and IOS support)
Video	High Definition	2*2MP
	Image resolution	Main code stream: 1920*2160@12fps; Substream: 800*896@12fps
	Minimum illumination	0.01 LUX/pro series
	Lens	3.6mm(standard)
	Perspective	92 °
	Turn video	Flip up and down/flip side to side
lighting	Light control mode	Starlight full color/intelligent warning/infrared night vision
	Number of lights	8 red lights +4 white lights
PTZ	PTZ control	Rotation Angle level :355°; Vertical :90°
	Turn PTZ	Flip up and down/flip side to side
Audio	Coding standard	G.711
	Mitou	support
	Two-way Speech	support
Record management	Video file size	≈6G/ day
	Record Mode	Manual video recording, dynamic detection video recording, timing
	Video storage	TF card/cloud
	storage	Cloud Storage +TF Local Video recording (128GB Max)
	Remote playback	support
	Image capture	support
Network	WIFI	2.4G WIFI 802.11b/g/n
	Pairing	hartlink distribution network addition, AP hotspot addition, QR code s
	Network Protocol	TCP/IP, ONVIF, RTSP
extension	Reset key	support
	Human tracking	support
	360degree coordinate	support
power supply	Power	DC 5V 1.6A
	power interfac	Micro Type-A
work environment	Suitable place	outdoor、Home、shop、School、factory;
	Installation mode	Wall hanging, lifting, flat
	Working	-20℃ — +55℃
	Working humidity	10% — 90%