

Model:		*4MP cloud camera (excluding TF Card) X 1 * Specification X1 * Screw pack X1 * stents X1 * Power adapter X1 * Power cord X1	
FT-P400SMT40F			
Specification parameter			
Camera	Material	2.5inch PTZ ,Aluminum alloy die casting	
	Sensor	XM530 3MP 1/2.8 CMOS	
	Minimal Illumination	0.001Lux @(F1.4,AGC ON) ,0 Lux with IR	
	Shutter	Adaption	
	Lens	3.6mm	
	Angle	Horizontal 0°-355°,Vertical 0°-90°	
	Lens Port	M12	
	Day and Night Switch	Automatic switching,ICR infrared filter type	
	Infrared Distance	30 Meters	
	DNR	2D/3D DNR	
	WDE	D-WDR	
Compression Standard	Video Compression	Smart H.265	
	H.264 Code Type	Main Profile	
	Video Compression Code Rate	Adaptive Bit-rate	
	Audio Compression	ACC	
	Audio Compression Code Rate	Adaptive Bit-rate	
Image	Max. Resolution	HD: 2288*1288	
	FPS	15fps, Network transmission frame rate adaptation	
	Image Setting	Mirror,flip	
	BLC	Support	
Network Function	Intelligent Alarming	Input:Humanoid detection ,humanoid tracking ,humanoid tracking	
	Configuration	SmartConfig,AP configuration,Manually add	
	Port Agreement	Cloud privacy aggrement,ONVIF	
	General Function	Anti flicke,double stream,mirror,password protection,watermark	
Port	Storage Interface	Micro SD card(maximum128G)	
	Power Interface	Φ5.5 round head power interface	
	Wired Interface	Support	
Wireless Parameters	Wireless Standard	IEEE802.11b, 802.11g, 802.11n	
	Frequency	2.4 GHz ~ 2.4835 GHz	
	Channel Bandwidth	Support 20MHz	
	Safety	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK	
	Transmission Rate	11b:11Mbps, 11g : 54Mbps, 11n : 150Mbps	
General	Operating Conditions	-10 ℃ ~ 45 ℃, humidity less than 95% (non-condensing)	
	Power Supply	DC12V±10%	
	Dimension	23*21.5*12.5cm	
	Weight	1.5kg	
	Power Consumption	12W MAX	
	APP	ICSEE	