

图纸发布类别：正式归档图纸

(TYPE C接口)

成品尺寸	80x720mm
展开图尺寸:	80x720mm
公差:	±1mm

单位:mm

智能有线网Pro

产品使用说明书与三包卡

产品规格

产品名称	智能有线网Pro
产品型号	THP10-Z-X
电源输入	5V/1A/1A
工作温度	-10℃~+45℃
工作湿度	[10%~90%RH(31℃±1℃)]
额定功率	<0.5W
接口	1个RJ45 10/100/1000Mbps 1个USB
产品尺寸	90.00mm×92.33mm
产品重量	约14.5g
无线协议	ZigBee, Thread

产品介绍

智能有线网Pro作为支持Matter的物联网连接网关，具有强大的本地化处理和多设备稳定连接的能力，可便捷地提供有线、智能能源和家庭安全生态链的支持，使用户可以迅速部署智能设备控制设备，轻松实现更多样的场景应用，为用户提供便捷化智能家居体验。

状态指示灯 复位键 网络线接口 电源线接口

使用准备

- 手机连接有线网Pro时，请确保手机和网关处于同一个网络中，以保证手机与网关之间的有效连接。

手机 有线网Pro

- 下载并打开App

扫描左侧二维码或在应用商店搜索“智能有线网”，下载安装智能生活App。如第一次安装时，请点击“去获取”按钮按提示操作，如已有账号，则点击“登录”按钮。

智能生活App

添加设备

- 将智能有线网Pro接入电源，并连接网络线和路由器。
- 将网关与一个指示灯长亮（如需重置，长按复位键5s以上后再长亮）。

使用说明

- 添加设备

网关成功添加后即可添加子设备，请参考APP上的指引操作。
- 重置网关

长按网关按钮约15s以上重置设备，设备初始化完成后会重新进入配网状态，重置后需重新添加网关下的设备。
- 提示：
 - 1.添加网关前请确保手机已连接2.4G频段的Wi-Fi网络。
 - 2.为了连接便捷，请保持手机靠近网关，并确保手机和网关处于同一Wi-Fi网络。
 - 3.如添加设备失败请重启后再次尝试连接，请保持网关按钮以上重置设备，重新添加。

保修政策

智能有线网Pro相关的售后服务严格按照《中华人民共和国消费者权益保护法》、《产品质量法》和《三包规定》执行。本产品三包有效期如下：

1. 自您签收之日起15日内，本产品出现产品性能故障，可免费享受退货或换货服务。
2. 自您签收之日起15日内，本产品出现产品性能故障，可免费享受退货或换货服务。
3. 自您签收之日起12个月内，本产品出现产品性能故障，可免费享受维修服务。

电子信息产品有毒有害物质申明

物质名称	有毒有害物质元素					
	铅(Pb)	汞(Hg)	镉(Cd)	六价铬(Cr6+)	多环芳烃(PAH)	多溴二噁英(PBDE)
PCBA	○	○	○	○	○	○

注：表中(Pb)(Hg)(Cd)(Cr6+)(PAH)(PBDE)均符合GB/T 26572-2012标准的要求。

○ 表示该有害物质在正常使用状态下符合国家强制性标准。

× 表示该有害物质在正常使用状态下符合国家强制性标准。

注：本产品有害物质含量符合GB/T 26572-2012标准的要求。

产品三包凭证(客户联)

客户姓名：_____ (先生/小姐) 联系方式：_____

客户地址：_____ 购机日期：_____

产品三包凭证(商家联)

客户姓名：_____ (先生/小姐) 联系方式：_____

客户地址：_____ 购机日期：_____

产品合格证

本产品符合GB/T 26572-2012标准的要求。

检验员：_____

日期：_____

Smart Wired Gateway Pro

Product Manual and Warranty Certificate

Product Specifications

Product Name	Smart Wired Gateway Pro
Product Model	THP10-2X
Input Power	5 V=1mA (—Direct Current)
Working Temperature	-10℃ ~+45℃
Working Humidity	10% to 90% RH (non-condensing)
Standby Power	0.5W
Internet Port	10/100Mbps Ethernet
Product Size	90.0 mm x 90.0 mm x 23.0 mm
Net Weight	About 74.5 g
Wireless Protocol	ZigBee, Thread

Product Description

As the Internet of Things connection hub supporting the Matter protocol, the smart wired gateway Pro has local management and the ability of stable operation of multiple devices, it can connect devices such as home automation, smart energy and home security systems, and use mobile phones to remotely view or control devices, and it can diversify scene automation and provide users with convenient intelligent experience.

Indicator Description

Indicator Description	Product status	Indicator status
Network pairing indicator	Connected Router	Indicator on
	Router not connected	Indicator off
Status indicator	Distributed network	Indicator off
	Undistributed network	Indicator on
	System startup	Indicator flashing

Diagram showing the status indicator and network pairing indicator on the gateway device.

Diagram showing the reset button and network port on the gateway device.

Preparation

1. Connect your mobile phone to the WiFi network.
Connect your mobile phone and the gateway to the same network to ensure effective connectivity between them.

Diagram showing a mobile phone connected to a router, which is connected to a gateway.

2. Download and open the App
Search for "Smart Life" in the App store or scan the QR code in the manual to download and install the App. Press the "Register" button register an account if this is your first time use. If you already have an account, press the "Login" button.

QR code for Smart Life App

Add Device

1. Power on the gateway and connect it to the router through the network cable.

2. Ensure that both indicators of the gateway are on. (If reset is required, press and hold the reset button for more than 5s before releasing)

Diagram showing the gateway device with both indicators on.

Instructions

1. Add Sub-device
The sub-device can be added after the gateway is successfully added. Please refer to the instructions on the APP to add the sub-device.

2. Reset network
Press and hold the gateway button for more than 5 seconds to reset the device. After the initialization of the device is completed, the device will on distribution network state again, and repeat the steps of (Add Device)

3. Note:
1. Please ensure that your phone is connected to the 2.4GHz Wi-Fi network before adding a gateway.
2. In order to make the connection more smooth, please try to keep the phone close to the gateway and ensure that the phone and the gateway are in the same Wi-Fi network.
3. If the device fails to be added or is not in the distribution network state after power on, please press and hold the gateway button for more than 5 seconds to reset the device and add it again.

Please read the instruction manual carefully before using the product

Packing List

- Smart Wired Gateway Pro x 1
- Power cable x 1
- Net cable x 1
- Instruction manual x 1

版本	物料编号	变更者	变更时间	版本升级原因描述
1.0				原始版本

材质	105g铜版纸	客户 中性 (TYPE C接口)	产品名称	智能有线网关Pro (TYPE C接口)	物料名称	智能有线网关Pro (TYPE C接口)- 中性-说明书-中英文	设计	大川
印刷色	单印灰		型号	THP10-Z-X	物料编号		审核	pony
加工工艺	风琴9折页, 正反印刷		设计编码				时间	20230721
接合方式	/							