






尺寸: 50x78mm（折页）

材质: 80g 双铜

印刷: 彩色

易微联SQ510A水浸传感器

Zigbee Water leakage detector  *Please read this manual carefully before use and keep it for future reference.	Specifications: Input voltage: DC3V LR03 Static current: ≤10uA Alarm current: ≤15mA Low-Voltage indication: ≤2.5V Zigbee frequency: 2.400GHz-2.484GHz Detection: Water-sensor detector Installation: Wall-mounted Working temperature: -10°C ~ +50°C Working humidity: Max 95%RH	How to use: 1. Push the mounting bracket downward and take out the bracket, then insert the battery. 	2. Put the battery into the battery bin and place it according to the graphics in the battery bin. After two batteries are loaded, the indicator light always on and then off. 
2	3	4	

3. Download "eWeLink" APP in app store or google play store, or scan the following QR code. (Zigbee detector can not work independently, it has to connect eWeLink gateway to use)  Android/iOS	4. Register with mobile phone number, click "My Home" interface "+" or click "Add Devices" in the middle blank. choose quickly add,click add one device → input WiFi password → automatically search device → click gateway for configuration (gateway must in configuration status) 	5. After gateway adding success, click APP to add zigbee sub detector, take a pin to long press reset key for more than 5 seconds till indicator light flashes quickly means into pairing status. APP shows searching device, devices will be find within 30 seconds, click to pair with gateway, indicator light off. 	6. After paired success, click icon of water detector into interface page, Put the probe into water, APP shows Water leakage is detected, if need send messages please click "..." in top of right corner to enable message sending. 
5	6	7	8