

K	技术要求: 1. 尺寸:展开450*65mm, 折后45*65mm 2. 材质:105g铜版纸 3. 颜色:四色印刷 4. 工艺:手风琴10折页 5. 环保要求: 所有材料及工艺需满足欧盟WEEE和RoHS指令要求				原材料 <table><tr><th>测试项</th><th>测试要求</th><th>测试项</th><th>测试要求</th></tr><tr><td>☒ RoHS检测</td><td>第三方认证报告 (有效期一年)</td><td>☐ 低温存储 (-40℃)</td><td></td></tr><tr><td>☐ 球压试验 (125℃/70℃)</td><td></td><td>☐ 冷热冲击 (-40~70℃)</td><td></td></tr><tr><td>☐ 灼热丝试验 (850℃/650℃)</td><td></td><td>☐ 百格测试</td><td></td></tr><tr><td>☐ UV老化测试 (72H/48H)</td><td></td><td>☐ RCA试验 (100圈/150圈..)</td><td></td></tr><tr><td>☐ 冰醋酸测试 (3min/5min)</td><td></td><td>☐ 铅笔硬度测试 (3H/4H..)</td><td></td></tr><tr><td>☐ 盐雾试验 (24/36/48H..)</td><td></td><td>☐ 酒精耐摩擦测试</td><td></td></tr><tr><td>☐ 高温存储 (70℃)</td><td></td><td>☐ 镭雕/丝印附着力测试</td><td></td></tr><tr><td>☒</td><td></td><td>☐</td><td></td></tr></table>				测试项	测试要求	测试项	测试要求	☒ RoHS检测	第三方认证报告 (有效期一年)	☐ 低温存储 (-40℃)		☐ 球压试验 (125℃/70℃)		☐ 冷热冲击 (-40~70℃)		☐ 灼热丝试验 (850℃/650℃)		☐ 百格测试		☐ UV老化测试 (72H/48H)		☐ RCA试验 (100圈/150圈..)		☐ 冰醋酸测试 (3min/5min)		☐ 铅笔硬度测试 (3H/4H..)		☐ 盐雾试验 (24/36/48H..)		☐ 酒精耐摩擦测试		☐ 高温存储 (70℃)		☐ 镭雕/丝印附着力测试		☒		☐		PC, 松诺白色 <table><tr><th>尺寸</th><th>等级</th><th>A</th><th>B</th><th>C</th></tr><tr><td>0<L≤3</td><td></td><td>±0. 05</td><td>±0. 10</td><td>±0. 15</td></tr><tr><td>3<L≤6</td><td></td><td>±0. 10</td><td>±0. 15</td><td>±0. 20</td></tr><tr><td>6<L≤16</td><td></td><td>±0. 15</td><td>±0. 25</td><td>±0. 35</td></tr><tr><td>16<L≤30</td><td></td><td>±0. 20</td><td>±0. 30</td><td>±0. 45</td></tr><tr><td>30<L≤120</td><td></td><td>±0. 25</td><td>±0. 35</td><td>±0. 50</td></tr><tr><td>120<L≤315</td><td></td><td>±0. 30</td><td>±0. 50</td><td>±0. 80</td></tr><tr><td>0<L≤10</td><td>±1°</td><td>50<L≤120</td><td>±0. 5°</td><td></td></tr><tr><td>10<L≤50</td><td>±0. 3°</td><td>120<L≤400</td><td>±0. 15°</td><td></td></tr></table>				尺寸	等级	A	B	C	0<L≤3		±0. 05	±0. 10	±0. 15	3<L≤6		±0. 10	±0. 15	±0. 20	6<L≤16		±0. 15	±0. 25	±0. 35	16<L≤30		±0. 20	±0. 30	±0. 45	30<L≤120		±0. 25	±0. 35	±0. 50	120<L≤315		±0. 30	±0. 50	±0. 80	0<L≤10	±1°	50<L≤120	±0. 5°		10<L≤50	±0. 3°	120<L≤400	±0. 15°		制图日期		黎业军 2024/05/30		物料编码:		单位		比例		图框	
	测试项	测试要求	测试项	测试要求																																																																																																					
	☒ RoHS检测	第三方认证报告 (有效期一年)	☐ 低温存储 (-40℃)																																																																																																						
	☐ 球压试验 (125℃/70℃)		☐ 冷热冲击 (-40~70℃)																																																																																																						
	☐ 灼热丝试验 (850℃/650℃)		☐ 百格测试																																																																																																						
	☐ UV老化测试 (72H/48H)		☐ RCA试验 (100圈/150圈..)																																																																																																						
☐ 冰醋酸测试 (3min/5min)		☐ 铅笔硬度测试 (3H/4H..)																																																																																																							
☐ 盐雾试验 (24/36/48H..)		☐ 酒精耐摩擦测试																																																																																																							
☐ 高温存储 (70℃)		☐ 镭雕/丝印附着力测试																																																																																																							
☒		☐																																																																																																							
尺寸	等级	A	B	C																																																																																																					
0<L≤3		±0. 05	±0. 10	±0. 15																																																																																																					
3<L≤6		±0. 10	±0. 15	±0. 20																																																																																																					
6<L≤16		±0. 15	±0. 25	±0. 35																																																																																																					
16<L≤30		±0. 20	±0. 30	±0. 45																																																																																																					
30<L≤120		±0. 25	±0. 35	±0. 50																																																																																																					
120<L≤315		±0. 30	±0. 50	±0. 80																																																																																																					
0<L≤10	±1°	50<L≤120	±0. 5°																																																																																																						
10<L≤50	±0. 3°	120<L≤400	±0. 15°																																																																																																						
L													00. 00. 07. 0340				MM		1:1		/																																																																																				
																	投影视角				K																																																																																				
																	图号		第1/1页																																																																																						
																	版本		V1. 1																																																																																						
																	物料名称:																																																																																								
																	SNZB-05P 快速指南						L																																																																																		
1				2				3				4				5				6				7				8				9				10				11				12				13				14				15				16																																													