


37*68mm → 111*68mm

RAIN SENSOR - use manual - A black and white photograph of a rectangular rain sensor device with vertical ridges. Logos for Tuya, WiFi, and Zigbee. Please read the instructions carefully	Product Introduction This product is one of the smart home series, with rain detection function, provides real-time and intuitive data for the smart home system, realizes linkage control with other smart home products, and effectively improves the user's intelligent experience. The product is designed for ultra-low power consumption, long battery life, and has a low battery alarm function, so users do not need to worry about the battery life of the product. Thank you for purchasing and using this product, please follow the instructions!	Product Parameters: Product Name: Rain Sensor Connection Mode: 2.4GWi-Fi / Zigbee 3.0 Battery: AAA*2 (not inclede) Operating Temperature: -10~50°C Product Life: 3years (Zigbee) / 1years (WiFi) Product Dimension: 2.4*2.1*7cm / 0.9*0.8*2.8in Packing List: Rain Sensor X1 Instruction manual X1 Double-sided adhesive X1
--	--	---

Download APP: Scan the QR code below to download and install, install and register to log in. A QR code with a blue house icon in the center. *Note: WiFi version: 2.4G WiFi connection is required. Zigbee version: Need to use with Tuya gateway.	Add Device: Wi-Fi Version 1. Connect the mobile phone Wi-Fi(2.4G signal)/ turn on Bluetooth. 2. Enter the distribution network state 3. Open the APP and click "Add Device" 4. Discover the device, click Add, and wait until the device is added. 5. To display the completion of the addition,click "Next" and click "Finish" Zigbee Version 1. Open the APP, click the "+" sign in the upper right corner, find the Zigbee gateway and access it, then add the Rain sensor	(make sure the gateway, Rain sensor and cell phone are connected to the same WiFi). 2. Cell phone connects to WiFi password network, enter the password and click confirm, 3. The interface jumps to the [being connected] interface, wait for the device to complete the network allocation, and enter the add device interface. Installation & Reset: Push the back cover upward, put in the battery, the LED light will blink. Long press 8 seconds to reset. A diagram showing a battery cover with a blue arrow pointing to a button labeled 'Reset Button'.
--	--	--